

# Pathos 2021 – 2022

<b>Classic One MKIII</b>	<b>22995,-</b>
integrated amplifier 2 x 70W@ 8 Ohm - class A / AB - Hybrid technology 4 line inputs RCA and 1 balanced XLR, purely resistive volume control) <b>matt black top panel and steel-brushed case, padouk or black front panel</b>	
<b>Classic Remix</b>	<b>23995,-</b>
integrated amplifier 2 x 70W@ 8 Ohm - class A / AB - Hybrid technology - fully balanced 3 line inputs RCA and 1 balanced XLR, pre out S/PDIF and USB "B" type port digital inputs optional ( HiDac/HiDac MK2 required ) <b>Top cover special finish: lacquered white, black , red. Tillæg: 3500,-</b>	
<b>Logos MKII</b>	<b>35995,-</b>
integrated amplifier 2 x 110W@ 8 Ohm - class A / AB - Hybrid technology 5 line inputs RCA and 2 balanced XLR, pre out, S/PDIF and USB digital inputs optional ( HiDac required ) Purely resistive remote controlled volume control. <b>Available finishes: padouk wood or black front panel</b>	
<b>Kratos</b>	<b>69995,-</b>
integrated amplifier 2 x 200WRMS@ 8 Ohm - 2 x 350WRMS @ 4 Ohm 2 balanced XRL line, 5 unbalanced RCA line, 1 balanced XRL direct to the power amp Hidak Mk2 and Phono stage RIAA for MM/MC optional 1 Pre out stereo unbalanced RCA - 1 Pre out stereo balanced XLR <b>Available finishes: padouk wood or black front panel</b>	
<b>InPol Remix MkiI</b>	<b>38995,-</b>
integrated amplifier 2 x 20W@ 8 Ohm, 2 x 35W@ 4 Ohm Pure class A - double INPOL technology – fully balanced – digital Bias/gain setting technology 4 line inputs RCA and 1 balanced XLR, pre output inverting and non-inverting, S/PDIF and USB "B" type port digital inputs optional (HiDac MK2 required) <b>Top cover special finish: lacquered white, black , red. Tillæg: 3500,-</b>	
<b>TT Anniversary</b>	<b>49995,-</b>
integrated amplifier 2 x 35W@ 8 Ohm - Pure class A - INPOL technology Purely resistive optical/relays remote controlled volume; remote controlled input selector 4 line inputs RCA and 1 balanced XLR, sub out <b>Available finishes: padouk wood or black side panels</b>	
<b>TT Remote Reference</b>	<b>46995,-</b>
integrated amplifier 2 x 35W@ 8 Ohm- Pure class A - INPOL technology Purely resistive optical/relays remote controlled volume 5 line inputs RCA, 1 tape out <b>Available finishes: padouk wood or black side panels</b>	
<b>InPol2 MkiI,</b>	
integrated amplifier 2 x 50W@ 8 Ohm - Pure class A - double INPOL technology - fully balanced Purely resistive relays remote controlled volume 4 line inputs RCA and 2 balanced XLR S/PDIF and USB "B" type port digital inputs optional (HiDac MK2 required)	
	<b>74995,-</b>

## InPol Heritage

[spørg om pris](#)

integrated amplifier without compromises ! 2 x 80W@ 8 Ohm, 2 x 130W@ 4 Ohm Pure class A –  
double INPOL technology - fully balanced - digital Bias/gain set technology Purely resistive relays  
remote controlled volume 4 line inputs RCA and 2 balanced XLR, pre output inverting and  
non-inverting, S/PDIF and USB “B” type port digital inputs optional ( HiDac MK2 required

**Available finishes: Black with padouk or black fascia**

## InPower MkII

79995,-

monoblock power amplifier Type: entirely balanced, Double INPOL® power amplifier in pure class A

Feedback: absent Output power: 120 W @ 8 Ohm Input impedance: 100 kOhm

Frequency response: 5Hz ÷ 60kHz ± 0.3 dB Signal/noise ratio: 98 dB

THD: < 0.4% up to maximum power. Pris pr. styk ! **Available finishes: Black with padouk or black fascia**

## Adrenalin

[spørg om pris](#)

monoblock power amplifier 200W @ 8 Ohm - Pure class A - double INPOL technology - intrinsically

balanced design Accurate power supply inductive-capacitance Tubes: 2x ECC83 12AX7 SOVTEK,

1x 6H30 SOVTEK 1 line inputs RCA and 1 balanced XLR. Pris pr. styk ! **Available finishes: black and grey, matt metallic**

## InControl Mk2

49995,-

stereo preamplifier Pure class A, fully balanced Input: 2 balanced XLR, 4 unbalanced RCA

Output: 1 balanced XLR, 1 unbalanced RCA. **Padouk wood or black front panel; black or gray side panels**

## Synapse

[spørg om pris](#)

stereo preamplifier Two-stage construction - intrinsically balanced design - original volume block,

tubes 4 x 6H30 Input: 3 Balanced XRL, 3 line RCA Output: 2 Balanced XRL. **Available finishes: matt metallic gray**

## New InTheGroove

12995,-

MM/MC phono stage Ultra low noise design - two-stage construction Selectable gain –

Input load selectable - balanced output. **Available finishes: grey or black with grey or black buttons**

## Converto MK2

12995,-

D/A converter, preamplifier and headphone amplifier 32 bit/384KHz with DSD and I2S - class A - fully

balanced S/PDIF inputs - USB “B” type port digital inputs. **Available finishes: grey or black with grey or black buttons**

## Converto MK2 RR

14995,-

D/A converter, preamplifier and headphone amplifier 32 bit/384KHz with DSD and I2S - class A - fully

balanced S/PDIF inputs - USB “B” type port digital inputs, remote. **Finishes: grey or black with grey or black buttons**

## Aurium

10995,-

headphone amplifier 2 x 3,6W @ 16 Ohm - output impedance. **Grey or black with grey, black or red buttons and knob**

## **InPol EAR**

**34995,-**

headphone amplifier and preamplifier 4 line inputs RCA and balanced XLR, pre output inverting

and non inverting S/PDIF and USB "B" type port digital inputs optional ( HiDac MK2 required ). **Top cover special finish:**

**lacquered white, black , red. Tillæg: 3500,-**

## **HiDac MK2 (til indbygning)**

D/A converter built-in Module with additional digital connections, including HiDac Mk2 board S/PDIF inputs –

USB "B" type port digital inputs

Standard: available for Classic Remix, InPol Remix MKII, Heritage, EAR, InPoL2 MkII, InControl

**4995,-**

Logos-HiDAC: available for Logos only

**4995,-**

Kratos HiDac MK2 module D/A converter Pcb with converter D/A 32bit/384KHz with DSD and I2S codec to be

integrated 1 optic S/PDIF input - 1 RCA S/PDIF input - 2 USB "B" type port digital inputs Available for Kratos

**4995,-**

**forbehold for trykfejl og ændringer i specifikationer / priser.**